

AL series

油雾器
Lubricator



规格/Specification

符号/Symbol

保证耐压力 Ensured Pressure Resistance	1.5MPa(15kgf/cm ²)
最高使用压力 Highest Working Pressure	1.0MPa(10kgf/cm ²)
环境及流体温度 Ambient and Temperature	5~60℃
建议用油 Recommended Oil Use	透平1号油/Turbine NO.1 Oil ISOVG32
容器材料 Container Material	聚碳酸脂/Polycarbonate
防护罩 Protective Cover	有/Available

型号 /Model	规格 Specifications					配件/Accessories
	*油滴最小流量 (Minimal Flow of Oil Drop)(L/min)	**额定流量 (Rated Flow)(L/min)	**接管口径 (Port Size)(G)	杯容量(cm) /Bowl Capacity	重量 (Weight)(kg)	托架 /Bracket
AL2000-01	15	800	1/8	15	0.18	B240
AL2000-02			1/4			
AL3000-02	30	1700	1/4	50	0.27	B340
AL3000-03	40		3/8			
AL4000-03	40	5000	3/8	130	0.5	B440
AL4000-04	50		1/2			
AL4000-06	50	6300	3/4	130	0.57	B540
AL5000-06	190	7000	3/4	130	1.1	B640
AL5000-10			1			

*供应压力为0.5MPa(5.1kgf/cm²)情况下,由滴流量为5滴/分钟,透平1号油
ISOVG32,温度20℃情况下。

*Under the circumstance that the supply pressure is 0.5MPa(5.1kgf/cm²), Oil drop flow is 5drops/minute, use of turbine No.1Oil and 20℃ temperature.


**供应压力为0.5MPa(5.1kgf/cm²),口径为0.03MPa(0.3kgf/cm²)情况下。

Under the circumstance that the supply pressure is 0.5MPa(5.1kgf/cm²) and step down is 0.03MPa(0.3kgf/cm²).


**接管口径有G、NPT两种可选。
G、NPT两种口径均有。

Both G and NPT port size are available.

外形尺寸图/Overall Dimension Drawing (mm)



AL2000



AL5000

型号Model	口径 (Port Size)(G)	A	B	C	D	F	G	H	J	K	L	M	P
AL2000	1/8~1/4	40	121.5	38	40	30	27	22	5.4	8.4	40	2.3	40
AL3000	1/4~3/8	53	142	38	53	40	40	23	6.5	8	53	2.3	56
AL4000	3/8~1/2	70	177	41	70	50	54	26	8.5	10.5	70	2.3	73
AL4000-06	3/4	75	177	39	70	50	54	25	8.5	10.5	70	2.3	73
AL5000	3/4~1	90	254	45	90	66.5	66	35	11	13	90	3.2	90



F-TEC

C-10

www.F-TEC.cn