

# AC series

空气过滤器组合 (三联件)  
F.R.L Combination



## 规格/Specification

## 符号/Symbol

保证耐压力/Ensured Pressure Resistance	1.5MPa(15kgf/cm <sup>2</sup> )
最高使用压力/Highest Working Pressure	1.0MPa(10kgf/cm <sup>2</sup> )
环境及流体温度/Ambient and Fluid Temperature	5~60℃
*过滤精度/*Filter Precision	25 um
建议用油/Recommended Oil Use	透平1号油/Turbine NO.1 Oil ISOVG32
容器材料/Container Material	聚碳酸酯/Polycarbonate
防护罩/Protective Cover	有/Available
调压范围/Pressure Regulating Range	0.05~0.85MPa(0.5~8.5kgf/cm <sup>2</sup> )
阀型/Valve Type	带溢流型/With Overflow

还有5、50 um可供选择。/\*5、50um available in addition

型号 Model	规格 Specifications							配件/Accessories		
	过滤器 /Filter	减压阀 /Regulator	油雾器 /Mist Separator	*额定流量 /Rated Flow (L/min)	*接管口径 /Port Size (G)	压力表口径 /Pressure Gauge Size	重量 /Weight (kg)	托架 /Bracket (2个)	压力表 /PressureGauge	
AC2000-01	AF2000	AR2000	AL2000	500	1/8	1/8	0.74	Y20L	G36-10-01	
AC2000-02					1/4					
AC2500-02	AF3000	AR2500	AL3000	1500	1/4	1/8	1.04	Y30L		
AC2500-03					3/8					
AC3000-02	AF3000	AR3000	AL3000	2000	1/4	1/8	1.18	Y30L		
AC3000-03					3/8					
AC4000-03	AF4000	AR4000	AL4000	4000	3/8	1/4	2.14	Y40L		
AC4000-04					1/2					
AC4000-06	AF4000-06	AR4000-06	AL4000-06	4500	3/4	1/4	2.47	Y50L		G46-10-02
AC5000-06	AF5000	AR5000	AL5000	5000	3/4	1/4	3.28	Y60L		
AC5000-10					1					

\*供应压力为0.7MPa(7.1kgf/cm<sup>2</sup>)设定压力为0.5MPa(5.1kgf/cm<sup>2</sup>)的情况下

\*Under the circumstance that the supply pressure is 0.7MPa(7.1kgf/cm<sup>2</sup>)and set pressure is 0.5MPa(5.1kgf/cm<sup>2</sup>)

\*\*接管口径另有RC、NPT螺纹可供选择:

Rc.and NPT port size are available

